

**PEXP143T-1.5-2**


**EXPLOSION PROOF ELECTRIC MOTOR**

**NEMA PREMIUM EFFICIENCY**

**TOTALLY ENCLOSED FAN COOLED; EXPLOSION PROOF ENCLOSURE**

**CLASS I DIVISION I GROUP C & D; CLASS II DIVISION I GROUP F & G**

**OPERATING TEMP CODE T3C**



**DIMENSIONS**

HP	RPM	Frame	MOUNTING														
			A	B	C	D	G	H	J	E	2E	2F1	2F2	O	P	T	BA
1.5	3600	143T	7.00	5.20	12.60	3.50	0.50	0.34	1.40	2.75	5.50	4.00	5.00	7.10	6.95	0.00	2.25

Shaft Extension, Key Set						Conduit Box		Bearings		Mount
U	V	R	S	ES	N-W	AA	AB	DE	ODE	
0.875	2.00	0.771	0.188	1.41	2.25	0.75	6.10	6205-ZZ	6205-ZZ	F1

**BEARING LUBRICATION:** The bearings come lubricated with Mobil Polyrex EM Polyurea Grease.










**PEXP143T-1.5-2**
**EXPLOSION PROOF ELECTRIC MOTOR**
**NEMA PREMIUM EFFICIENCY**
**TOTALLY ENCLOSED FAN COOLED; EXPLOSION PROOF ENCLOSURE**
**CLASS I DIVISION I GROUP C & D; CLASS II DIVISION I GROUP F & G**
**OPERATING TEMP CODE T3C**
**PERFORMANCE DATA**

HP	RPM	Frame	Voltage	Frequency (Hz)	Full Load S.F.	Insulation Class	NEMA Design	Slip (%)	NEMA Code	Enclosure Type	IP Rating	Max. Ambient	Oper Temp Code	Max. KVAR
1.5	3511	143T	208-230/460	60	1.15	F	B	2.5	M	TEXP	55	40° C	T3C	0.8

Amps (460V)		Max. Amps (208V)	Efficiency (%)				Power Factor			Torque (ft-lb)			DE Bearing	ODE Bearing	Connection	Weight (lbs.)
FLA	LRA	60HZ	100%	75%	50%	Min.	100%	75%	50%	FLT	LRT %	BDT %				
1.9	20.0	4.1	84.0	85.1	83.5	81.5	0.85	0.81	0.69	2.3	175	250	6205-ZZ	6205-ZZ	9 Lead 2Y/Y	73

**NAME PLATE**

 										<b>CONNECTION DIAGRAMS</b>  208-230V   460V 						
<b>PREMIUM EFFICIENT EXPLOSION PROOF MOTOR</b>																
CAT NO:		PEXP143T-1.5-2		FRAME		143T		PHASE		3						
DE BRG		6205-ZZ		ODE BRG		6205-ZZ		CONN.		9 Lead 2Y/Y						
MAX AMB.		40° C		INS. CLASS		F		RATING		CONT WEIGHT 73						
USABLE ON 208V 60HZ AT		4.1		MAX AMPS		SER										
DIVISION 1 CLASS I GROUP C D CLASS II GROUP F G						OPER TEMP CODE T3C										
60 HERTZ DATA	HP		1.5		RPM		3511		HP		1.5		RPM		2926	
	VOLTS				208-230/460				VOLTS				190/380			
	F.L. AMPS				4.1 - 3.7 / 1.85				F.L. AMPS				4.5/2.3			
	S.F. AMPS				2.1				S.F. AMPS				4.5/2.3			
	S.F. 1.15 DESIGN B CODE M								S.F. 1.0 DESIGN B CODE N							
	NEMA NOM.EFF. 84.0 % P.F. 0.85								NEMA NOM.EFF. 82.8 % P.F. 0.85							
	NEMA MIN.EFF. 81.5 %								NEMA MIN.EFF. 79.4 %							
	MAX. KVAR 0.8								LUB. Mobil Polyrex EM							
<small>General purpose use on industrial machinery installed in damp, dusty or dirty environments. These motors are designed for use in hazardous locations defined by class and group.</small>												  CC 041B				
Hernando, Mississippi																

	<b>ELECTRIC MOTORS FOR HAZARDOUS LOCATIONS</b>
	CLASS I DIVISION I GROUP C D, CLASS II DIVISION I GROUP F G NO. CCXXXXX E310089

**APPLICATIONS:**

General purpose use on pumps, fans, blowers, compressors, conveyors, material handling and other industrial machinery installed in damp, dusty or dirty environments. These motors are designed to be used in hazardous locations as defined by class and group.